

### SPECIFICATIONS

General Data			Unit	FEATURES
Overall Dimensions	Ø217x88	mm		Steel Basket
Nominal Power Handling	300	W		Non-Pressed Paper Cone, Treated Cloth Surround
Maximum Power	600	W		Dome Paper Dustcap
Sensitivity	96	dB		High Temperature 1.75" CCAW Voice Coil
Frequency Response	90~15000	Hz		High Performance 50oz Ferrite Magnet Structure
Cone Material	Non-Pressed Paper			
Basket	Steel			
Net Weight	3.38	kg		
Electrical Data				
Nominal Impedance	4	Ohm		
DC Resistance	3.2	Ohm		
Voice Coil and Magnet Parameters				
Voice Coil Diameter	44.7	mm		
Voice Coil Height	8	mm		
Magnetic Gap Height	6	mm		
Voice Coil Robbin	Kapton			
Number of Layers	2L			
T-S Parameters				
Suspension Compliance	183.871µM/N	Cms		
Mechanical Q Factor	9.176	Qms		
Electrical Q Factor	0.462	Qes		
Total Q Factor	0.439	Qts		
Moving Mass	15.914	Mms		
Eq. Cas AIR Loaded	16.152L	Vas		
Resonant Frequency	93.041Hz	Fs		
Effective Piston Area	248.720cm <sup>2</sup>	SD		

### Dimensions

