

Model:RS-GH12
30 CM Subwoofer Speaker



SPECIFICATIONS

General Data			Unit	FEATURES
Overall Dimensions	320x134		mm	* Steel Basket
Nominal Power Handling	350		W	* Pressed Paper Cone With Foam Surround
Maximum Power	1500		W	* High Temperature 2" Voice Coil
Sensitivity	87		db	* Ferrite Magnet Structre
Frequency Response	40-1000		Hz	
Cone Material	Pressed Paper Cone			
Basket	Steel			
Net Weight	4		kg	
Electrical Data				
Nominal Impedance	4/4X2		ohm	
DC Resistance	3.7/3.7X2		ohm	
Voice Coil and Magnet Parameters				
Voice Coil Diameter	50.8		mm	
Voice Coil Height	57		mm	
HE magnetic Gap Height	23		mm	
Voice Coil bobbin	AL			
Number of Layers	4L			
Magnet System Type	Ferrite			
T-S Parameters				
Suspension Compliance	0.14/0.09		Cms	
Mechanical Q Factor	7.8/7.1		Qms	
Electrical Q Factor	0.79/0.84		Qes	
Total Q Factor	0.72/0.76		Qts	
Moving Mass	124/120		Mms	
Eq.Cas AIR Load	53.5/51		Vas	
Resonant Frequency	38.2/39.1		Fs	
Effective Piston Area	514.7cm ²		SD	

Dimensions

