

Model: RS-JB6

16 CM Component Speaker



SPECIFICATIONS

General Data		Unit	FEATURES
Overall Dimensions	Ø159 x61	mm	Stamp Steel Basket
Nominal Power Handling	60	W	Silver Grey Paper Cone, Butyl Rubber Surround
Maximum Power	220	W	Silver Grey Paper Dustcap
Sensitivity	90	dB	High Temperature Voice Coil, High Performance Ferrite Magnet Structure
Frequency Response	70~20000	Hz	Include Titanium Dome Tweeter & Crossover

Cone Material	Silver Grey Paper	
Basket	Steel	
Net Weight	0.9	kg

Electrical Data		
Nominal Impedance	3	Ohm
DC Resistance	2.2	Ohm

Voice Coil and Magnet Parameters		
Voice Coil Diameter	25.9	mm
Voice Coil Height	10	mm
Magnetic Gap Height	5	mm
Voice Coil Robbin	Kapton	
Number of Layers	2L	

T-S Parameters		
Suspension Compliance	471.100µM/N	Cms
Mechanical Q Factor	7.744	Qms
Electrical Q Factor	0.655	Qes
Total Q Factor	0.604	Qts
Moving Mass	12.106	Mms
Eq. Cas AIR Loaded	9.746L	Vas
Resonant Frequency	66.645HZ	Fs
Effective Piston Area	12.070cm ²	SD

