

Model:RS-KP15

38 CM Subwoofer Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	396x194	mm
Nominal Power Handling	1500	W
Maximum Power	3000	W
Sensitivity	88	db
Frequency Response	35-500	Hz
Cone Material	Non Pressed Paper Cone	
Basket	Aluminium	
Net Weight	11	kg
Electrical Data		
Nominal Impedance	2X2/2X4	ohm
DC Resistance	2X1.8/2X3.2	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	61.1	mm
Voice Coil Height	40	mm
HE magnetic Gap Height	10	mm
Voice Coil bobbin	AL	
Number of Layers	4L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	77.14/90.45	Cms
Mechanical Q Factor	4.97/4.26	Qms
Electrical Q Factor	0.84/0.91	Qes
Total Q Factor	0.72/0.76	Qts
Moving Mass	300.5/298.1	Mms
Eq.Cas AIR Load	66.5/61.3	Vas
Resonant Frequency	37.1/38.6	Fs
Effective Piston Area	813cm <sup>2</sup>	SD

FEATURES
* Aluminium Basket
* Non Pressed Paper Cone With Treated Foam Surround
* High Temperature 2.5" Voice Coil
* Ferrite Magnet Structure

Dimensions

