

Model:RS-VW15

30 CM Subwoofer Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	392x246	mm
Nominal Power Handling	3000	W
Maximum Power	6000	W
Sensitivity	95	db
Frequency Response	30-500	Hz
Cone Material	Non Pressed Paper Cone	
Basket	Aluminium	
Net Weight	32.5	kg
Electrical Data		
Nominal Impedance	2X1/2X2	ohm
DC Resistance	2X1.0/2X2.0	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	99.2	mm
Voice Coil Height	45	mm
HE magnetic Gap Height	12	mm
Voice Coil bobbin	AL	
Number of Layers	4L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	171/185	Cms
Mechanical Q Factor	7.84/7.46	Qms
Electrical Q Factor	1.43/1.64	Qes
Total Q Factor	1.14/1.35	Qts
Moving Mass	425/375	Mms
Eq.Cas AIR Load	168.5/159.6	Vas
Resonant Frequency	57.5/60	Fs
Effective Piston Area	779cm ²	SD

FEATURES
* Aluminium Basket
* Non Pressed Paper Cone With Treated Foam Surround
* High Temperature 4" Voice Coil
* Ferrite Magnet Structre

Dimensions

