

Model:RS-VX15

30 CM Subwoofer Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	392x246	mm
Nominal Power Handling	1200	W
Maximum Power	2400	W
Sensitivity	88	db
Frequency Response	40-500	Hz
Cone Material	Non Pressed Paper Cone	
Basket	Aluminium	
Net Weight	12	kg
Electrical Data		
Nominal Impedance	2X2/2X4	ohm
DC Resistance	2X1.8/2X3.6	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	76.5	mm
Voice Coil Height	45	mm
HE magnetic Gap Height	12	mm
Voice Coil bobbin	AL	
Number of Layers	4L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	0.13	Cms
Mechanical Q Factor	5.2	Qms
Electrical Q Factor	0.8	Qes
Total Q Factor	0.69	Qts
Moving Mass	360	Mms
Eq.Cas AIR Load	61	Vas
Resonant Frequency	39	Fs
Effective Piston Area	774.4cm ²	SD

FEATURES
* Aluminium Basket
* Non Pressed Paper Cone With Treated Foam Surround
* High Temperature 3" Voice Coil
* Ferrite Magnet Structure

Dimensions

