

Model: SX-TA30

3.75" PRO BULLET TWEETER



**SPECIFICATIONS**

| General Data           |          | Unit |
|------------------------|----------|------|
| Overall Dimensions     | 101.5*80 | mm   |
| Nominal Power Handling | 100      | W    |
| Maximum Power          | 200      | W    |
| Sensitivity            | 101      | dB   |
| Frequency Response     | 5K-20K   | Hz   |
| Cone Material          | PEI      |      |
| Basket                 | AL       |      |
| Net Weight             | 1,37     | kg   |

| FEATURES                     |
|------------------------------|
| 3.75" PRO BULLET TWEETER     |
| DIAPHRAGM MATERIAL: PEI      |
| RATED POWER: 100W            |
| MAX. POWER: 200W             |
| FREQUENCY RESPONSE: 5K-20KHz |
| SENSITIVITY: 101dB           |

| Electrical Data                  |        |     |
|----------------------------------|--------|-----|
| Nominal Impedance                | 6      | Ohm |
| DC Resistance                    | 6      | Ohm |
| Voice Coil and Magnet Parameters |        |     |
| Voice Coil Diameter              | 37,6   | mm  |
| Voice Coil Height                | 2      | mm  |
| Magnetic Gap Height              | 2      | mm  |
| Voice Coil Robbin                | kapton |     |
| Number of Layers                 | 2      |     |

**Dimensions**

